



## ZENITH YK Series Vibrating Screen features and technical data

ZENITH is one of the biggest manufacturers in aggregate processing machinery for the sand & gravel, quarry, mining, construction and recycling industries. Headquarter of ZENITH is located in Shanghai, China and now we have two manufacturing bases as our strong support. The equipment includes crusher, mobile crusher, conveyor, **screening machine**, sand washing machine, track mounted mobile crusher, crushing equipment, mill equipment, complete aggregate crushing equipment, jaw crusher, cone crusher, impact crusher, complete quarry equipment, and so on. We will provide the right equipment according to the customer's requirements, and help customers to choose the location of the production line, equipment installation, training of workers, as well as on-site help and after-sales service.

This is ZENITH YK Series **Vibrating Screen** features and technical data:

### YK Series Vibrating Screen Features

1. High screening efficiency
2. High capacity and reliability
3. Long bearing lifetime
4. Easy maintenance
5. Pivoting motor bases
6. Special eccentric shaft create circular throw action

## YK Series Vibrating Screen Technical Data

Model	Screen Size (mm)	Layers	Mesh Size (mm)	Feeding Size (mm)	Capacity (t/h)	Power (kw)	Motor Model	REV (r/min)	Amplitude (mm)	Angle (°C)	Machine Size (mm)
2YK1237	1200×3700	2	3-50	≤200	7.5-80	4-15	Y160L-4/15	970	8	20	4010×2250×2660
3YK1237	1200×3700	3	3-50	≤200	7.5-80	4-15	Y160L-4/15	970	8	20	4010×2250×3140
2YK1548	1500×4800	2	5-50	≤400	50-208	4-15	Y160L-4/15	970	8	20	5120×2590×3060
3YK1548	1500×4800	3	5-50	≤400	50-250	4-15	Y160L-4/15	970	8	20	5120×2590×3540
2YK1848	1800×4800	2	5-80	≤400	50-260	4-18.5	Y180M-4/18.5	970	8	20	5120×2950×3060
3YK1848	1800×4800	3	5-80	≤400	50-300	4-18.5	Y180M-4/18.5	970	8	20	5120×2950×3540
2YK1860	1800×6000	2	5-80	≤400	50-300	4-18.5	Y180M-4/18.5	970	8	20	6260×2950×3480
3YK1860	1800×6000	3	5-80	≤400	50-350	4-22	Y180L-4/22	970	8	20	6260×2990×3960
2YK2160	2100×6000	2	5-150	≤400	100-500	4-22	Y180L-4/22	730	6-8	20	6270×3410×3670
3YK2160	2100×6000	3	5-100	≤400	100-500	4-30	Y200L-4/30	730	6-8	20	6270×3470×4100
2YK2460	2400×6000	2	5-150	≤400	150-700	4-37	Y225S-4/37	730	6-8	20	6270×3770×3610
3YK2460	2400×6000	3	5-150	≤400	150-700	4-37	Y225S-4/37	730	6-8	20	6270×3790×4100